

Dedicated Speaker Processors (*Mix* January 2004)

Specs At a Glance

Mfg./Model	I/O	Dimensions	AES I/O	Ports	Smaart	Front Panel Control	Presets	Max. Slope	Para. EQs	Delay	Limiters	Resolution	Dyn. Range	List
Apex Intelli-X	4x8	1U x 11.3 inches deep	2 in	232, 485, USB	no	yes	40	48 dB/octave	8 in*, 8 out	500 ms	opt. Servo	24/48	110 dB	\$3,995
Ashly 4.24C	4x8	1U x 6 inches deep	no	232, MIDI	yes	yes	30	48 dB/octave	6 in, 4 out	682 ms	Full	24/48	110 dB	\$1,899
Behringer DCX2496	3x6	1U x 8.5 inches deep	1 in	232, 485	no	yes	60	48 dB/octave	3 in, 6 out	582 ms	Zero-attack	24/96	113 dB	\$439
BSS MiniDrive FDS-336T	2x6	1U x 8 inches deep	no	232, MIDI	yes	yes	60	48 dB/octave	37 total	635 ms	2-stage	24/48	108 dB	\$1,500
BSS Omnidrive	3x6	1U x 11.5 inches deep	1 in	232, 485, MIDI	yes	yes	50	52 dB/octave	50 total	2,624 ms	Dual	24/96	112 dB*	\$3,799
Compact plus T														
dbx DriveRack PA	2x6	1U x 5.8 inches deep	no	none	no	yes	25u + 25	24 dB/octave	GEQ in, 3 out	0 ms	PkStop+	24/48	107 dB	\$750
dbx DriveRack 260	2x6	1U x 5.8 inches deep	no	232, 485	yes	yes	25u + 25	48 dB/octave	9 in**, 4 out	1,000 ms	PkStop+	24/48	110 dB	\$1,000
dbx DriveRack 480	4x8	2U x 12.2 inches deep	no	232, 485, MIDI	yes	yes	20u + 20	48 dB/octave	9 in**, 4 out	682 ms	PkStop+	24/48	112 dB	\$3,400
DEQX PDC-2.6	2x6	1U x 17 inches deep	1 in (out opt.)	232, USB	no	no	4	300 dB/octave	10 out	n/a	n/a	24/96	110 dB	\$3,500
Electro-Voice Dx38	2x4	1U x 14.7 inches deep	no	232, MIDI, opt. 485	no	yes	30u + 50	24 dB/octave	5 in, 4 out	900 ms	Full	24/48	115 dB	\$1,798
JBL DSC260A	2x6	1U x 8 inches deep	no	MIDI	yes	yes	60	48 dB/octave	30 total	635 ms	2-stage	24/48	108 dB	\$2,149
Klark Teknik DN9848	4x8	1U x 12 inches deep	no	232, 485	yes	yes	6u + 32	48 dB/octave	96 total	1,000 ms	LookAhead	24/48	114 dB	\$4,665
Lake Contour	2x6	1U x 15.8 inches deep	no	232, Ethernet	yes	no	unlimited	brick wall	unlimited	2,000 ms	RMS+SC	24/96	109 dB	\$4,900
Sony SRP-F300	2x6	1U x 14 inches deep	1 I/O	232 (x2)	yes	semi	50	36 dB/octave	11 in**, 3 out	1,000 ms	2-stage	24/96	110 dBA	\$1,950
Xilica DLP4080	4x8	1U x 10 inches deep	I/O opt.	232, MIDI	no	yes	64	24 dB/octave	8 in, 6 out	500 ms	Full	24/48	115 dB	\$1,350
XTA DP226	2x6	1U x 11.8 inches deep	I/O opt.	232, MIDI	yes	yes	40	24 dB/octave	8 in, 5 out	650 ms	Fast	24/48	110 dB	\$3,995
XTA DP6i	2x6	1U x 11.8 inches deep	I/O opt.	232, 485, MIDI	yes	semi	4FP (40)	24 dB/octave	8 in, 5 out	650 ms	Fast	24/48	110 dB	\$2,795
									**or GEQ, *plus GEQ				*117 AES	